

IN THE CLAIMS

1. (Currently Amended) An email method for an intranet web server ~~that, the email method comprising:~~

at the intranet web server, automatically generating ~~generates email on behalf of from~~ an intranet user; and

at the intranet web server, queuing ~~queues~~ the automatically-generated email in an email spooler;

at the intranet web server, sending from ~~where~~ the automatically-generated email is sent to a mail server for delivery to an intended recipient; and ~~and wherein~~

at the intranet web server, if the automatically-generated email is returned from the mail server that was as undeliverable to the ~~an intended recipient is returned to the intranet web server, then~~ the email method includes ~~comprising~~ the acts of:

(a) fetching an email address for the intranet web server's system administrator;

(b) verifying normal operation of the email spooler by examining each email queued in the email spooler to determine the pendency of each email within the email spooler;

(c) emailing the system administrator regarding an abnormal operation if act (b) verifies that the email spooler is not operating normally;

(d) processing each undeliverable email to determine whether it was returned because of a problem with the email itself or because of a problem with the mail server;

(e) resending the undeliverable email to the intended recipient if act (d) determines that an undeliverable email was returned because of a problem with the mail server; and

(f) sending the undeliverable email to the originating intranet user if act (d) determines that an undeliverable email was returned because of a problem with the undeliverable email itself.

2. (Original) The method of claim 1, wherein act (a) comprises fetching the email address from a database.

3. (Original) The method of claim 1, wherein acts (a) through (f) are repeated periodically.

4. (Original) The method of claim 3, wherein acts (a) through (f) are repeated at least every 30 minutes.

5. (Currently Amended) The method of claim 1, wherein act (b) comprises:
~~examining each email queued in the email spooler to determine its pendency within the email spooler; and~~
emailing the system administrator regarding ~~each~~ this email's pendency if an email's pendency within the email spooler exceeds a normal pendency period,
wherein the normal pendency period comprises a predefined time period including two minutes.

6. (Original) The method of claim 5, wherein acts (a) through (f) are repeated periodically, and wherein act (b) further comprises:
deleting this email from the email spooler and emailing the system administrator that a persistent email spooler problem has been detected if an email has been previously detected as exceeding the normal pendency period.

7. (Original) The method of claim 6, wherein act (b) further comprises:
restarting the email spooler if an email has been previously detected as exceeding the normal pendency period.

8. (Original) The method of claim 1, wherein acts (a) through (f) are repeated periodically, and wherein act (e) comprises resending the undeliverable email to the intended recipient only if it has not been previously resent to the intended recipient a predetermined number of times.

9. (Currently Amended) A machine readable medium having stored thereon data representing instructions for an intranet's web server, wherein the machine readable medium comprising:

at the intranet web server, automatically generating generates email from an intranet user; and

at the intranet web server, queuing queues the automatically-generated email in an email spooler;

at the intranet web server, sending from where the automatically-generated email is sent to a mail server for delivery to an intended recipient; and -and-wherein

at the intranet web server, if the automatically-generated email is returned from the mail server as that was undeliverable to the an intended recipient is returned to the intranet web server, then the instructions adapting the intranet web server to perform an email method comprising the acts of:

(a) fetching an email address for the intranet web server's system administrator;

(b) verifying normal operation of the email spooler by examining each email queued in the email spooler to determine the pendency of each email within the email spooler;

(c) emailing the system administrator regarding an abnormal operation if act (b) verifies that the email spooler is not operating normally;

(d) processing each undeliverable email to determine whether it was returned because of a problem with the email itself or because of a problem with the mail server;

(e) resending the undeliverable email to the intended recipient if act (d) determines that an undeliverable email was returned because of a problem with the mail server; and

(f) sending the undeliverable email to the originating intranet user if act (d) determines that an undeliverable email was returned because of a problem with the undeliverable email itself.

10. (Original) The machine readable medium of claim 9, wherein the stored data is such that act (a) comprises fetching the email address from a database.

11. (Original) The machine readable medium of claim 9, wherein the stored data is such that acts (a) through (f) are repeated periodically by the web server.

12. (Original) The machine readable medium of claim 11, wherein the stored data is such that acts (a) through (f) are periodically repeated at least every 30 minutes by the web server.

13. (Currently Amended) The machine readable medium of claim 9, wherein the stored data is such that act (b) comprises:

~~examining each email queued in the email spooler to determine its pendency within the email spooler, and~~

if an email's pendency within the email spooler exceeds a normal pendency period, emailing the system administrator regarding each this email's pendency,

wherein the normal pendency period comprises a predefined time period including two minutes.

14. (Original) The machine readable medium of claim 13, wherein the stored data is such that acts (a) through (f) are repeated periodically, and wherein act (b) further comprises:

deleting this email from the email spooler and emailing the system administrator that a persistent email spooler problem has been detected if an email has been previously detected as exceeding the normal pendency period previously.

15. (Original) The machine readable medium of claim 14, wherein the stored data is such that act (b) further comprises:

restarting the email spooler if an email has previously been detected as exceeding the normal pendency period.

16. (Original) The machine readable medium of claim 9, wherein the stored data is such that acts (a) through (f) are repeated periodically, and wherein act (e) comprises

resending the undeliverable email to the intended recipient only if it has not been previously resent to the intended recipient a predetermined number of times.

17. (Currently Amended) A system comprising:

a ColdFusion intranet web server configured to automatically generate email from an intranet user and queue the automatically-generated email in a ColdFusion email spooler from where the automatically-generated email is sent to an SMTP mail server for delivery to an intended recipient, and wherein automatically-generated email that was undeliverable to an intended recipient is returned to the ColdFusion server, the ColdFusion server being further configured to perform a method comprising the acts of:

(a) verifying that the SMTP mail server is on-line;

if the SMTP mail server is on-line:

(b) fetching an email address from a relational database for the ColdFusion server's system administrator;

(c) verifying normal operation of the ColdFusion email spooler by examining each email queued in the ColdFusion email spooler to determine the pendency of each email within the ColdFusion email spooler;

(d) emailing the system administrator regarding an abnormal operation if act (c) verifies that the ColdFusion email spooler is not operating normally;

(e) processing each undeliverable email to determine whether it was returned because of a problem with the email itself or because of a problem with the SMTP mail server;

(f) resending the undeliverable email to the intended recipient if act (e) determines that an undeliverable email was returned because of a problem with the SMTP mail server; and

(g) sending the undeliverable email to the originating intranet user if act (e) determines that an undeliverable email was returned because of a problem with the undeliverable email itself.